



EAF ULTIMATE

WELCOME TO THE NEW GENERATION

The combination and integration of the best EAF technologies and design features has led to the development of a new generation of electric arc furnaces – the EAF Ultimate.

This high-tech power package is characterized by superhigh power input, high shell and roof design, high efficiency automation, high-speed furnace equipment movement, performance-enhancing oxygen and carbon injection technology, short tap-to-tap times, and reliable operation. Its modular design, quick-change components, and easy access for simplified maintenance maximize furnace availability and steel output.

PROCESS AND OPERATIONAL FEATURES

- Superhigh power input (up to 1.5 MVA/t)
- Latest oxygen and carbon injection technology with RCBs (Refining Combined Burners)
- Furnace design for one-bucket scrap charging
- Automatic prepositioning of scrap bucket
- Continuous-feed systems for HBI and DRI (hot or cold)
- Hot-metal charging facilities
- Contact-free steel temperature measurements
- Automatic tap control with video camera
- Automatic slag detection system during tapping
- Taphole- and door-cleaning robots

**HIGH FLEXIBILITY
WITH CHARGE
MATERIALS**

DESIGN AND EQUIPMENT FEATURES:

- Robust and reliable equipment
- Gantry with single-point roof-lifting device
- Prismatic roller guide system for electrode masts
- High-capacity current-conducting electrode arms in copper-clad box design
- State-of-the-art electrode control system
- Copper or combi-panels with high-speed cooling water flow
- High furnace shell and roof for improved postcombustion
- All bottom tapping systems (EO-EBT, EBT, RBT, OBT)
- Crane with two auxiliary hooks for quick electrode exchange
- Split-shell design for fast exchange of shell sections
- Automatic taphole filling device

PLANT DATA

Design parameters

Tap weight	145 t
Scrape charge	1 bucket
Transformer	155 MVA +20 %

Performance values

Power-on time	31 min
Power-off time	7 min
Tap-to-tap time	38 min
Heats per day	> 37
Productivity	230 t/h

Consumption values

Electricity	340 kWh/t
Electrodes	1.2 kg/t
Oxygen	41 Nm ³ /t
Carbon charged	10 kg/t
Carbon injected	8 kg/t



320 ton EAF Ultimate at Çolakoğlu, Turkey

MAIN BENEFITS

- High degree of flexibility with charge materials
- High reliability and availability
- Proven and profitable technology for any steel route (flat and long)
- Highest productivity resulting in dilution of fixed costs
- High-impedance furnace
- Arc voltage up to 1,650 V
- Proven low consumption values for energy, electrodes, refractories, etc.
- Minimum maintenance with the use of heavy mill-type components

SELECTED REFERENCES

- Acciaieria Arvedi S.p.A, Italy
- Kaluga – NLMK Group, Russia
- Çolakoğlu Metalurji A.S., Gebze, Turkey
- Revda – Maxi Group, Russia
- MMK – Magnitogorsk Iron and Steel Works, Russia

Primetals Technologies Austria GmbH
A Group Company of Mitsubishi Heavy Industries

Turmstrasse 44 | 4031 Linz | Austria
primetals.com

Order No. T02-0-N363-L4-P-V5-EN
Printed in Linz | © 2023

The information (including, e.g., figures and numbers) provided in this document contains merely general descriptions or characteristics of performance based on estimates and assumptions which have not been verified. These estimates and assumptions have to be analyzed on a case-to-case basis and might change as a result of further product development. It is no representation, does not constitute and/or evidence a contract or an offer to enter into a contract to any extent and is not binding upon the parties. Any obligation to provide and/or demonstrate respective characteristics shall only exist if expressly agreed in the terms of the contract.

Primetals Technologies excludes any liability whatsoever under or in connection with any provided information, estimates and assumptions. The provided information estimates and assumptions shall be without prejudice to any possible future offer and/or contract.

Any information provided by Primetals Technologies to the recipient shall be subject to applicable confidentiality obligations and shall be used by the recipient at their own convenience and at their sole risk.

Primetals is a trademark of Primetals Technologies Ltd.