



## MULPIC®

# PLATE COOLING TECHNOLOGY CHINA STEEL CORPORATION KAOHSIUNG, TAIWAN

**Project start: April 2014**  
**FAC completion: May 2016**

In April 2014, Primetals Technologies received an order to supply a new Direct Quench (DQ) Plate Cooling System based on MULPIC technology as part of a modernisation project for the China Steel Corporation (CSC) 4.1m Plate Mill, with the aim to increase their product mix as well as improve the quality of their final products.


The scope of modernization of existing cooling machine by installing two four metre MULPIC® DQ cooling banks in front of an existing laminar cooling section. The scope of supply also included a new roller table, drives and automation systems for the new MULPIC® cooling sections as well as control of the customer supplied DQ Pumps.

### MULPIC® TECHNOLOGY SOLUTION

MULPIC® technology is an 'in-line' cooling system with the capacity to achieve the cooling rates and temperature drops required for Accelerated Cooling (ACC) and Direct Quench (DQ) cooling for a wide range of plate thicknesses.

### MAIN BENEFITS

- Hybrid cooling solution combining the powerful MULPIC DQ cooling banks with the existing Laminar Cooling sections is a fully automated and integrated mechatronic package.
- The installation of MULPIC® Technology allowed new steel grades including SUS304L Stainless Steel, high strength structural and wear resistance plates to be introduced.
- Improved product quality resulting from uniform and accurate MULPIC® cooling control
- Robust design and ease of maintenance also means reduced down time and reduced requirement for frequent maintenance.



Mechanical configuration



MULPIC Headers + Laminar Hybrid Cooling in action

## SPECIFICATION

### CSC MULPIC® - Plate Cooling System

Machine Length	8 m divided into 2 Cooling Banks.
No. of Headers per Cooling Bank	4 Top + 4 Bottom
Cooling Headers Width	4,100 mm
Cooled Plates Thickness Range	10 ~ 220 mm
Top Headers Height Adjustment	500 ~ 1,200 mm
Edge Masking Width Range	1,000 mm ~ 4,300 mm
Water Supply Pressure at TOP DQ (Pump Supply)	5.0 bar
Max. Flow DQ (Pump fed)	4,100 m <sup>3</sup> /hr per Bank

## OPERATION PRINCIPLES

The MULPIC Level 2 Model controls the cooling for the new Sections as well as the existing Laminar Cooling Sections providing a hybrid cooling solution.

The intermediate Temperature and cooling rates of individual Sections are controlled.

Two (2) cooling operation modes are available:

- **DQ Only** - DQ flow applied in Banks A and B.
- **DGACC Hybrid** - DQ flow applied on Banks A and B, and ACC flow applied in the Laminar Cooling sections.

## TECHNICAL FEATURES

- Highly Dynamic, Fast & Accurate Flow Control
- Header Design, individual flow control - Flexibility
- Length Temperature Uniformity - better quality
- Width Temperature Uniformity - better quality
- Adaptive, Model-based Cooling Control

## PERFORMANCE

- FCT Accuracy (N=100) SD: **13°C** (G.V.: **16°C**).
- Cooling Rate Accuracy: **+/-10%** of target.
- Length Temperature Uniformity SD: **15.0°C**
- Width Temperature Uniformity SD: **10.0°C**

**Primetals Technologies Limited**  
A joint venture of Mitsubishi Heavy Industries and partners

Sheffield Business Park | Europa Link | Sheffield S9 1XU  
[primetals.com](http://primetals.com)

Order No. T04-0-N600-L3-P-V2-EN  
Printed in Linz | © 2020

The information (including, e.g., figures and numbers) provided in this document contains merely general descriptions or characteristics of performance based on estimates and assumptions which have not been verified. It is no representation, does not constitute and/or evidence a contract or an offer to enter into a contract to any extent and is not binding upon the parties. Any obligation to provide and/or demonstrate respective characteristics shall only exist if expressly agreed in the terms of the contract. These estimates and assumptions have to be analyzed on a case-to-case basis and might change as a result of further product development. Primetals Technologies excludes any liability whatsoever under or in connection with any provided information, estimates and assumptions. The provided information, estimates and assumptions shall be without prejudice to any possible future offer and/or contract. Any use of information provided by Primetals Technologies to the recipient shall be subject to applicable confidentiality obligations and for the own convenience of and of the sole risk of the recipient. Primetals is a trademark of Primetals Technologies Ltd.